



A brand of **TOTAL**

EVOLUTION 900 5W-50



Evolution 900 5W-50 is an ELF synthetic technology lubricant for Gasoline and Diesel car engines, and is particularly recommended for the most severe weather conditions.

APPLICATIONS

Gasoline and Diesel engines

• Intended for Gasoline and Diesel engines, with or without supercharging, in cars and light vans.

All times of year, particularly the most extreme seasons

• The viscosity grade 5W-50 permits use at any time of year and is particularly recommended in extreme weather conditions.

PERFORMANCES

International specifications

API: SG/CD

CUSTOMER BENEFITS

Optimum running in the most extreme temperatures

- Easy starting in both very cold and very hot weather.
- Excellent engine protection, particularly against wear in the timing system.
- Outstanding thermal stability and oxidation resistance, preventing any degradation even in heavy duty conditions.
- Immediate lubrication of engine parts during cold starts. Resulting in extended engine life.

CHARACTERISTICS

	Method	Units	SAE Grade 5W-50
Density at 15°C	ASTM D1298	kg/m ³	852
Viscosity at 40°C	ASTM D445	mm ² /s	115
Viscosity at 100°C	ASTM 445	mm ² /s	18,2
Viscosity index	ASTM D2270	-	177
Pour point	ASTM D97	°C	- 40
Flash point	ASTM D92	°C	220
B.N.	ASTM D2896	mgKOH/g	8,5

The typical characteristics mentioned represent mean values

